Endure

Construction	Scroll Loop Pile Carpet Tile
Yarn	100% Solution Dyed Nylon
Size	500mm x 500mm
Tiles per Carton	20pcs / 5.0m²
Pile Weight	800g/m²
Total Weight	4775g/m²
Pile Height	4.5mm
Total Thickness	7.5mm
Machine Gauge	1/10th
Backing	PVC
Electrical Properties	Antistatic
Electrical Propensity	0.2kV (ISO 6356)
Fire Rating	CRF ≥9.3kW/m² (AS ISO9239-1)
VOC Rating	<0.5 mg/m²/hour (ASTM D5116-06)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Underfloor Heating	Suitable
Colour Fastness	5/5 on Grey Scale (ISO105-B02)
Rating	Heavy Duty Commercial
Stair Rating	Suitable
Warranties	15 Year Commercial Warranty
Installation	Laying recommendation: Quarter Turn or Brick Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	CRI Green Label Certified Low VOC, Solution dying uses no water Quality Management ISO 9001 Environmental Management ISO 14001 Toitu Carbonreduce Organisation Certified ISO 14064-1

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A World of Perfect Choices