Forest Grove

Construction	Tufted Cut Pile Carpet
Yarn	100% Stainproof Solution Dyed Nylon
Width	4.0m
Standard Roll Length	30m
Yarn Weight	1000g/m² / 30oz/yd²
Total Weight	2190g/m²
Pile Height	8.5mm
Total Thickness	±10.5mm
Machine Gauge	1/10th
Primary Backing	Woven Polypropylene
Secondary Backing	FusionBac
Electrical Properties	Antistatic
Electrical Propensity	≤ 2.0kV (ISO 6356 & EN 1307)
Anti-allergenic Properties	Will not shed or pill. Resistant to mould & mildew.
Underfloor Heating	Suitable
Rating	Extra Heavy Duty Residential Medium Duty Commercial
Stair Rating	Suitable
Warranties	15 Year Residential (Stain Proof, UV Colourfast) 7 Year Commercial (Stain Proof, UV Colourfast)
Installation	Please contact Gilt Edge Industries for all adhesive and installation instructions. NB: If recommended adhesive is not used, claims will not be accepted. All seams must be sealed. Must be laid in accordance with AS/NZ Installation Standards.
Environmental	Greentag Certified GreenStar, Homestar™ WELL Building Standard® Product Health Declaration™ Eco-Wash™ Treatment Low VOC, Solution dying uses no water Environmental Management ISO 14001 Quality Management ISO 9001 Occupational Health and Safety Management ISO 45001

- For samples, range and warranty details please contact us on 0800 377 753 or belgotex.co.nz
- Chair pads are recommended under office chairs with roller castors to preserve appearance retention and to avoid premature and accelerated wear.
- Specifications are based on averages from manufacturing processes and may vary within normal industry tolerances: Width ±3mm, Pile Weight ±5%.
- Material supply and/or manufacturing processes may necessitate specification changes without notice. Such variations do not affect product performance.

Belgotex®

A World of Perfect Choices